

Kitsap County Training & Safety Officers Skill Guide

Skill Guide	
FSS-8-4	

RIT	- SCBA	Mask w	regulator	Swap	out
	- 3000	IVIGSIX VV	i egulatoi	JWap	UUI

Name: _				
Date:				

Description: This Skill Guide is intended to instruct and/or evaluate a RIT team performing a mask with regulator replacement on a downed firefighter.

Related Instructor Guide:

Performance Standards:

Asses	ssment & Protection		
	Working as a member of a RIT, replace a face mask of a downed firefighter with a RIT nask and regulator	air p	ack
Condi	itions: In a simulated IDLH atmosphere, wearing full PPE including SCBA, with com	plete	to
zero vi	isibility graduating dependent upon level of expertise the crew has with this scenario	-	
	Objectives	Р	F
	Open RIT air pack, remove mask with regulator attached to mask. Note: If mask is not attached, attach regulator to mask at this time.		
2. Ti	urn on RIT air bottle fully		
3. R	lemove helmet of downed firefighter		
4. Pt	ull Flash-hood back		
5. R	elease straps on downed firefighters mask		
6. Pt	ull mask up and off downed firefighter with regulator attached		
7. C	Confirm all straps of RIT air mask are fully extended		
8. Pt	rull RIT mask webbing over face piece of air mask		
9. Pt	rush air mask onto face and hold snugly		
	ake other hand and bring webbing over the head of downed firefighter and tighten traps starting at the top		
11 C	Confirm receipt of air to downed firefighter		
N	lote: If unconscious it may be necessary to open emergency bypass valve to assist		
	vith air intake by downed firefighter. Do not open emergency bypass fully as this will		
bl	leed too much air.		
12 R	eplace Flash hood and helmet ensuring chin strap is tight.		
	Convert downed firefighters SCBA to a harness and secure RIT pack to Downed refighters SCBA.		
Perfor	rmance Outcome; The downed Firefighter's SCBA mask is quickly replaced with a		
mask o	connected to the RIT Air Supply		

Evaluator Comments:	
	Evaluator Signature:



Kitsap County Training & Safety Officers Skill Guide



